

[54] **HAND HELD DATA ENTRY UNIT**

[76] Inventor: Dale H. Learn, Field Ter., Irvington, N.Y. 10533

[21] Appl. No.: 343,441

[22] Filed: Jan. 28, 1982

[51] Int. Cl.<sup>3</sup> ..... G06F 3/02

[52] U.S. Cl. .... 340/365 R; 340/365 S; 340/711; 340/825.19; 400/87

[58] Field of Search ..... 340/711, 712, 365 R, 340/365 VL, 825.19, 825.56, 365 S; 400/87, 88; 178/17 C

[56] **References Cited**

**U.S. PATENT DOCUMENTS**

3,651,512 3/1972 Summers ..... 340/365 VL  
4,007,443 2/1977 Bromberg et al. .... 340/711  
4,215,240 7/1980 Ostrowski ..... 340/825.19  
4,241,521 12/1980 Dufresne ..... 340/825.19

**FOREIGN PATENT DOCUMENTS**

1417848 12/1975 United Kingdom ..... 400/87  
1475886 6/1977 United Kingdom ..... 340/712

Primary Examiner—Gerald L. Brigance  
Attorney, Agent, or Firm—McAulay, Fields, Fisher, Goldstein & Nissen

[57] **ABSTRACT**

A data entry unit has a board on which a matrix of cells are arranged, for example, twelve columns by four rows. When turned on, each column is sequentially illuminated in a continuous cyclic fashion. The illumination of a column indicates that the data associated with each of the four cells in that column is enabled. A handle attached to the board has at least four switches on it that can be readily manipulated by four fingers of the user's hand. When a column is illuminated, closing one of the four switches will complete the selection of the data in the corresponding one of the four cells of the illuminated column. This data may be stored or displayed or both. Each cell can be designed to correspond to two separate items of data, such as lower and upper case letters. In such a case, a further thumb actuated switch in the handle provides user selection for one of the two data phases of the cell.

12 Claims, 4 Drawing Figures

